

Dopisanie repozytorium non-free do pliku /etc/apt/sources.list, który ma wyglądać tak:

```
deb http://ftp.pl.debian.org/debian/ squeeze main non-free
deb-src http://ftp.pl.debian.org/debian/ squeeze main non-free

deb http://security.debian.org/ squeeze/updates main non-free
deb-src http://security.debian.org/ squeeze/updates main non-free

# squeeze-updates, previously known as 'volatile'
deb http://ftp.pl.debian.org/debian/ squeeze-updates main non-free
deb-src http://ftp.pl.debian.org/debian/ squeeze-updates main non-free
```

Lub możemy to zmienić za pomocą polecenia:

```
cat /etc/apt/sources.list | sed "s/main/main non-free/g" >
/etc/apt/sources.list.bak
mv /etc/apt/sources.list.bak /etc/apt/sources.list
```

Instalacja podstawowych pakietów:

```
apt-get update
apt-get install bzip2 unzip p7zip-full mc subversion subversion-tools telnet
tcpdump ntpdate git rsync net-tools aptitude
```

NTPDate

```
echo "2 * * * * root ntpdate -u pool.ntp.org > /dev/null" >> /etc/crontab
/etc/init.d/crond reload
```

From:

<https://kamil.kbejt.pl/> - **kamil.orchia.pl**

Permanent link:

https://kamil.kbejt.pl/doku.php?id=default_debian&rev=1533647969

Last update: **2025/01/11 18:57**

