

Plik init.d do Debiana:

```
#!/bin/bash

export JBOSS_HOME=/home/devel/jboss
export JBOSS_MODE=standalone
export JBOSS_PIDFILE=/var/run/jboss-as/jboss-as-standalone.pid
export JBOSS_CONSOLE_LOG=/home/devel/jboss/standalone/log/console.log
export STARTUP_WAIT=30
export SHUTDOWN_WAIT=30
export JBOSS_CONFIG=standalone-full.xml
export JBOSS_USER=devel
export JBOSS_SCRIPT=$JBOSS_HOME/bin/$JBOSS_MODE.sh

prog='jboss-as'

CMD_PREFIX=' '

start() {
    echo -n "Starting $prog: "
    if [ -f $JBOSS_PIDFILE ]; then
        read ppid < $JBOSS_PIDFILE
        if [ `ps --pid $ppid 2> /dev/null | grep -c $ppid 2> /dev/null` -eq '1' ]; then
            echo -n "$prog is already running"
            echo "Failure"
            echo
            return 1
        else
            rm -f $JBOSS_PIDFILE
        fi
    fi
    mkdir -p $(dirname $JBOSS_CONSOLE_LOG)
    cat /dev/null > $JBOSS_CONSOLE_LOG

    mkdir -p $(dirname $JBOSS_PIDFILE)
    echo "chown $JBOSS_USER $(dirname $JBOSS_PIDFILE)"
    chown $JBOSS_USER $(dirname $JBOSS_PIDFILE) || true
    #$CMD_PREFIX JBOSS_PIDFILE=$JBOSS_PIDFILE $JBOSS_SCRIPT 2>&1 >
    $JBOSS_CONSOLE_LOG &
    #$CMD_PREFIX JBOSS_PIDFILE=$JBOSS_PIDFILE $JBOSS_SCRIPT &

    if [ ! -z "$JBOSS_USER" ]; then
        su - $JBOSS_USER -c "LAUNCH_JBOSS_IN_BACKGROUND=1
        JBOSS_PIDFILE=$JBOSS_PIDFILE $JBOSS_SCRIPT -c $JBOSS_CONFIG" 2>&1 >
        $JBOSS_CONSOLE_LOG &
    fi

    count=0
    launched=false
```

```
until [ $count -gt $STARTUP_WAIT ]
do
    grep 'JBoss AS.*started in' $JBOSS_CONSOLE_LOG > /dev/null
    if [ $? -eq 0 ] ; then
        launched=true
        break
    fi
    sleep 1
    let count=$count+1;
done

echo "Success"
echo
return 0
}

stop() {
    echo -n $"Stopping $prog: "
    count=0;

    if [ -f $JBOSS_PIDFILE ]; then
        read kpid < $JBOSS_PIDFILE
        let kwait=$SHUTDOWN_WAIT

        # Try issuing SIGTERM

        kill -15 $kpid
        until [ `ps --pid $kpid 2> /dev/null | grep -c $kpid 2> /dev/null` -eq
'0' ] || [ $count -gt $kwait ]
        do
            sleep 1
            let count=$count+1;
        done

        if [ $count -gt $kwait ]; then
            kill -9 $kpid
        fi
    fi
    rm -f $JBOSS_PIDFILE
    echo "Success"
    echo
}

status() {
if [ -f $JBOSS_PIDFILE ];
then
    read kpid < $JBOSS_PIDFILE
    if [ "$kpid" == "" ];
    then
        echo "JBoss AS7 not running!"
    else
```

```
    echo "JBoss AS7 is running! PID ${kpid}"
  fi
else
  echo "JBoss AS7 is not running!"
fi
}

case "$1" in
start)
echo "Starting JBoss AS7..."
start
;;
stop)
echo "Stopping JBoss AS7..."
stop
;;
restart)
stop
start
;;
status)
status
;;
log)
echo "Showing server.log..."
tail -1000f ${JBOSS_HOME}/standalone/log/server.log
;;
console)
echo "Showing console.log..."
tail -1000f ${JBOSS_CONSOLE_LOG}
;;
*)
echo "Usage: /etc/init.d/jboss-as {start|stop|log|console}"
exit 1
;; esac
exit 0
```

From:

<https://kamil.kbejt.pl/> - **kamil.orchia.pl**

Permanent link:

https://kamil.kbejt.pl/doku.php?id=jboss_7&rev=1385125990

Last update: **2025/01/11 18:57**

